

Quick Stepper[®] Electro Hydraulic Power Pack “H1-LT”

- Quick Stepper Electro Hydraulic Power Pack H1-LT is a compact control unit for rotary/linear double and single acting where pressurized air is not available. Designed to solve most functions needed in an on/off control loop.
- The unit is very easy to use and can be easily configured by the built in switches.
- Remote installation gives an easy access for service and maintenance.
- No mechanical relays! SSR outputs assure high resolution and long lifetime.



Electro Hydraulic Power Pack
H1-LT-FSEH-PPOO

Available options:

- ✓ Actual position, mA out
- ✓ Alarm (HI or LO) with hysteresis & timer (1Pc)
- ✓ Digital inputs (1Pc)
- ✓ Digital outputs (1Pc)
- ✓ Emergency operation - Hand pump / Hand gear box
- ✓ Fail safe stop, open, close, or preset value
- ✓ Limit switches 2Pcs (External)
- ✓ Remote installation or built on actuator
- ✓ Time controlled open/close in 2 times zones. PosiRamp™
- ✓ QS-Lock™, Lock positioner and stop ramp
- ✓ QS-Output Tracking™, Write actual position to ramp set-point after lock
- ✓ QS-Timeout™, Pump control
- ✓ QS-PosiPump™ Hydraulic pump start/stop/off delay (SSR out 3)

Technical Specifications & Dimensions:		
Description:	Data:	
Analogue input 1 :	0/4-20 mA DC * 0/1-5VDC * 0/2-10VDC	Application examples: “Non ATEX”
Connection of electrical signals TB:1 (Ai/DC)	Quick Connector, 7-pole, FM, IP66	❖ Chemistry and Petro chemistry
Connection of electrical signals TB:2 (Di/Do)	Quick Connector, 7-pole, M, IP66	❖ District heating plants
Electrical connection	Quick Connector, 4-pole, FM, IP66	❖ Energy and water management
Control voltage	100–240 V~, 47–63 Hz	❖ Oil, gas and tank stations
Digital in / outputs	Optocoupler / Optocoupler NPN	• Critical fail safe application
Enclosure	IP66	• Two speed actuator control
Material, housing	Cast aluminium, Powder coated	
Output module	SSR, Ton/Toff time less than 100µs	
Standards of Compliance output module	CE Compliant with LVD 73/23/EEC	The only need of a control signal and main voltage makes the advantages compared to electro-mechanic or pneumatic actuators easy to realize.
Supply voltage standard version	100–240 V~, 47–63 Hz	
Temperature limits	-25...+40°C	
Weight	App. 11,5 kg	In addition are the extensive safety functions together with a high control force or torque which can be generated with very good accuracy.
Dimensions	H=230, W=280, D=110 mm	
CE Directives	EMC: EN50 081-2, EN50 082-2	

Do more with less!